

S09AQ NB0 / S12AQ NB0

- Eco Eye
- High Efficiency
- Optimized Cooling and Heating
- Allergy Free Filter
- Moisture Cooling
- Quick & Easy Installation
- Neo Plasma +Triple Filter



Model	INDOOR UNIT		S09AQ NB0	S12AQ NB0
	OUTDOOR UNIT		S09AQU UB0	S12AQU UB0
Cooling Capacity	(Min/Rating/Max)	W	0.89-2.50-3.70	0.89-3.50-4.04
		Btu/hr	3,070-8,530-12,620	3,070-11,900-13,800
Heating Capacity	(Min/Rating/Max)	W	0.89-3.2-5.5	0.89-4.00-6.00
		Btu/hr	3,070-10,920-18,760	3,070-13,600-20,470
Input	Cooling	W	545	875
	Heating	W	700	955
Running Current	Cooling	A	2.4	4.0
	Heating	A	3.1	4.3
Power Supply		ø,V, Hz	1/220-240/50	1/220-240/50
E.E.R	Cooling	W/W	4.6	4.0
		Btu/hrW	15.7	13.6
C.O.P	Heating	W/W	4.6	4.2
ENERGY Efficiency Class	Cooling/Heating		A/A	A/A
Noise Level (SoundPress,1m)	Indoor(H/M/L/Sleep)	dB(A)±3	38/33/23/19	39/33/23/19
	Outdoor, Max	dB(A)±3	45	45
Air Flow	Indoor, Max	m³/min(CFM)	12(423)	12.0(423)
	Outdoor, Max	m³/min(CFM)	33(1,165)	33(1,165)
Dehumidification Rate		l/h	1.1	1.3
Refrigerant charge(R410a)		g	R410A, 1,000(35.3)	R410A, 1,000(35.3)
SVC Valve	Liquid	mm(inch)	6.35(1/4)	6.35(1/4)
	Gas	mm(inch)	9.52(3/8)	9.52(3/8)
Dimensions (W*H*D)	Indoor	mm	895*285*195	895*285*195
Net Weight	Indoor	kg(lbs)	12(26.5)	12(26.5)
	Outdoor	kg(lbs)	35(77.2)	35(77.2)

Note: Specifications, design and feature are subject to change without prior notice.



Outdoor



2.6-3.5kW