

Parts list

Ref. to Diagram	Value	Name
MS		Meter system B-4C
R1	10.07 m Ω	28.622.851, rated sensitivity 450 μ A Shunt 10.07 m Ω \pm 1 % (30 A), 22.801.614, manganese sheet 0.5 \times 15 \times 88 mm
R2	40.2 m Ω	Shunt 40.2 m Ω \pm 1 % (6 A), 22.801.619, manganese wire 0.8 mm dia \times 173 mm
R3	0.151 Ω	Shunt 0.151 Ω \pm 1 % (1.5 A), 22.701.716
R4	0.807 Ω	Resistor 0.807 Ω \pm 1 %, 22.805.011
R5	120 k Ω	Carbon film resistor 120 k Ω \pm 1 %, 0.5 W
R6	27 k Ω	Carbon film resistor 27 k Ω \pm 1 %, 0.25 W
R7	150 k Ω	Carbon film resistor 150 k Ω \pm 1 %, 0.5 W
R8	300 k Ω	Carbon film resistor 300 k Ω \pm 1 %, 0.5 W
R9	18 Ω	Carbon film resistor 18 Ω \pm 1 %, 0.5 W
R10	62 k Ω	Carbon film resistor 62 k Ω \pm 5 %, 0.1 W
R11	330 k Ω	Carbon film resistor 330 k Ω \pm 1 %, 0.5 W
R12	330 k Ω	Carbon film resistor 330 k Ω \pm 1 %, 0.5 W
R13	3.3 k Ω	Carbon film resistor 3.3 k Ω \pm 5 %, 0.1 W
R14	56 k Ω	Carbon film resistor 56 k Ω \pm 1 %, 0.1 W
R15	5.6 k Ω	Carbon film resistor 5.6 k Ω \pm 1 %, 0.1 W