Manufacturer		DAIK
Outdoor unit		ARXC35AV1B
Indoor unit		ATXC35AV1B
Outdoor sound power level (dB)	dB(A)	60
Indoor sound level	dB(A)	00
The refrigerant (GWP)	UD(A)	R-32 (675.0)
		R 32 (073.0)
Cooling mode SEER		6.11
Energy efficiency class		0.11 A++
Annual electricity consumption	kWh/a	193
Design load Pdesignc	kWII/a	3.37
Heating mode: Average climate	K. VV	3.37
Design temperature = -10°C		
SCOP		4.00
Energy efficiency class		A+
Annual electricity consumption	kWh/a	768
Design load Pdesignh at -10°C	kW	2.19
Required back up heating capacity at -10°C	kW	0.390
Declared capacity at -10°C	kW	1.8
Heating mode: Warm climate Design temperature = 2°C		
SCOP		4.95
Energy efficiency class		A++
Annual electricity consumption	kWh/a	661
Design load Pdesignh at 2°C	kW	2.34
Required back up heating capacity at 2°C	kW	0.00
Declared capacity at 2°C	kW	2.34
Heating mode: Cold climate Design temperature = -22°C		
SCOP		
Energy efficiency class		
Annual electricity consumption	kWh/a	
Design load Pdesignh at -22°C	kW	
Required backup heating capacity at -22°C	kW	
Declared capacity at -22°C	kW	0