

PRODUCT INFO



PowerMust 400 USB



Features

- *Line-interactive* uninterrupted power supply with *automatic voltage regulation*
- Protection against data losses and damage to the sensible PC equipment caused by blackouts, brownouts, peaks and surges
- Built-in Smart RS-232 communication port and USB interface
- *Controlled Shut-down* function
- 3 protected outlets and a telephone jack for phone line and modem protection
- Delivered with UPS control software
- Light weight and compact design

Technical Data

Product Type	Uninterrupted power supply <i>line interactive</i>
Capacity	400 VA / 240 W
Input	
➤ Voltage	115 / 230 VAC
➤ Voltage Range	80 - 145VAC / 160 - 290VAC
Output	
➤ Voltage	115 / 230 VAC
➤ Voltage Regulation (Battery Mode)	± 10 %
➤ Frequency	50 or 60 Hz
➤ Frequency Regulation (Battery Mode)	± 1 Hz
➤ Output Wave Form	Modified sine wave
Battery	
➤ Type and Number	Maintenance-free rechargeable battery
Back-up Time (at half-load)	10 minutes
➤ Recharge Time	3-8 hours to 90% after complete discharge
Transfer Time (typical)	< 3 ms
Indicator	
➤ AC Mode	Green LED lights up
➤ Back-up Mode	Green LED is blinking
Audible Alarm	
➤ Back-up Mode	1 sound signal every 10 seconds
➤ Battery Low	1 sound signal every 0.5 second
➤ Overload	Continuous sound signal
Protection	Full Protection against discharge, overcharge and overload
Environment	
➤ Operating Temperature	0 °C - 40 °C
➤ Humidity	Relative, 0% ~ 90% (non condensing)
➤ Noise Level	AC mode: < 40 dB
Interface	
➤ Smart RS-232 Port	Windows 98/NT/2000/XP/2003 ; Linux, Sun Solaris, IBM, Aix, Compaq True64, SGI IRIX, FreeBSD, HP-UX
➤ USB Port	Windows 98/2000/ME/XP
Dimensions (L x W x H)	100 x 330 x 140 mm
Weight	6 kg
Accessory	Software, user guide, cables

All rights reserved. Subject to error and change without notice.

Mustek Optic-Computer & Communication International GmbH

Hansemannstr. 63, D-41468 Neuss Tel.: +49 (0)2131 1626-0 Fax: +49 (0)2131 103830